



P.C.B. LAYOUT

SPECIFICATIONS:

- Current Rating: 3AMP
- Insulator Resistance: 1000Meg ohms min
- Withstand Voltage: AC 500V
- Operating Temperature: -40° C ~ +85° C
- Max Processing Temp: 220° C for 3~5 seconds
- Contact Material: Brass
- Insulator Material: PBT Black
- Plating: G/F Plated over Nickel

Contacts Per Row	Dimensions		Contacts Per Row	Dimensions	
	A	B		A	B
2*2P	0.00	0.00	2*21P	53.74	50.80
2*3P	5.48	2.54	2*22P	56.28	53.34
2*4P	8.02	5.08	2*23P	58.82	55.88
2*5P	10.56	7.62	2*24P	61.36	58.42
2*6P	13.10	10.16	2*25P	63.90	60.96
2*7P	15.64	12.70	2*26P	66.44	63.50
2*8P	18.18	15.24	2*27P	68.98	66.04
2*9P	20.72	17.78	2*28P	71.52	68.58
2*10P	23.26	20.32	2*29P	74.06	71.12
2*11P	25.80	22.86	2*30P	76.60	73.66
2*12P	28.34	25.40	2*31P	79.14	76.20
2*13P	30.88	27.94	2*32P	81.68	78.74
2*14P	33.42	30.48	2*33P	84.22	81.28
2*15P	35.96	33.02	2*34P	86.76	83.82
2*16P	38.50	35.56	2*35P	89.30	86.36
2*17P	41.04	38.10	2*36P	91.84	88.90
2*18P	43.58	40.64	2*37P	94.38	91.44
2*19P	46.12	43.18	2*38P	96.92	93.98
2*20P	48.66	45.72	2*39P	99.46	96.52
	51.20	48.26	2*40P	102.00	99.06

topot 深圳市鑫冠辉电子有限公司

一般公差 COMMON TOLERANCES	图号 DWG NAME	绘图 FLOUT	比例 SCALE
X ±0.30	XGH-DWG-A-3089	LXW	1:1
X.X ±0.25	料号 PART NO	审核 CHECKED	单位 UNIT
X.XX ±0.20	PF1-M202-SBB-G0	LIYAN	mm
X.XXX ±0.15	品名 TITLE	核准 APPROVED	版次 REV.
ANGLE ±2°	排母2.54*8, 5 2*2P 180度 PC3, 0(Y端)	日期 DATE	页次 SHEET
	THIRD ANGLE PROJECTION:	2019-02-18	1/1
			图幅 SIZES
			A4

编号 DWG NO.	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN	版次 REV.